

2535 Rose Parkway
Sikeston, MO 63801
1-888-669-0003

Construction Trailer Specialists, Inc.

Rock Master: Elliptical



Specifications:

LENGTH:	22 FT. TO 40 FT.
SIDES:	46 INCHES TO 76 INCHES
BODY:	1/4" HARDOX 450 (175 KSI, 450 BRINELL HARDNESS)
NOSE & GATE:	3/16" HARDOX 450 (175 KSI, 450 BRINELL HARDNESS)
TOP RAIL:	3 1/2" X 5 1/2" X 1/4" HIGH STRENGTH STEEL 80,000 ROLL FORMED
LONGITUDINAL:	6" X 8" X 1/4" HIGH STRENGTH STEEL
BODY BRACES:	1/4" HIGH STRENGTH STEEL INTERNALLY STIFFENED
DRAFT ARMS:	5" X 3" X 1/4" STEEL TUBES WITH DROP LEGS
HOIST:	8"-5 STAGE INVERTED TRUNION MOUNT (CUSTOM HOIST)
SUSPENSION:	SINGLE POINT KEEPS ALL 8 TIRES ON THE GROUND HUTCH H-900 50,000 LB.
AXLES:	ROCKWELL AXLES 25,000 LB. HUB PILOTED
ABS BRAKES:	ABS BRAKES ON ONE AXLE 2S1M
TAILGATE:	HIGH LIFT OR BARN DOOR TAIL GATE MUD FLAPS MOUNTED ON BACK DOOR BRACING 5 3/4" X 3 3/4" X 3/16" HIGH STRENGTH STEEL, HIGH LIFT UP TO 60 INCHES BARN DOOR UP TO 76 INCHES
TIRES:	DUNLOP SP-160 11R X 24.5 RADIALS ON STEEL WHEELS
LADDERS:	FRONT AND REAR
FENDERS:	REAR BOLTED ON
WIRE HARNESS:	CUSTOM FIT AND FULLY SEALED (GROTE)
PAINT:	CARBOLINE PRIMER AND CARBOLINE PAINT (WHITE)

Need something really Big?



This is our Big One!

Built to the same specs as our elliptical shown above only **BIGGER!**

This trailer is 40 ft. long with 100" sides.

This combined with the 102" width allows for a whopping

85 cubic yard capacity.
