





DIMENSIONS

- 48 feet long
- 102 inches wide
- 42" rear deck height (light)
- flat load deck area-32'-2"
- 5' dovetail

WEIGHT

24,000 lbs. +/-3%

FEATURES

Mainframe	16" x 40# Mill Rolled I-beam w/ 3/4" x 6" strap under neck; 1/2" strap on bottom flange to front hanger
Crossmembers	10" x 12# Wide Flange Beams on 18" centers
Kingpin	20" king pin setting with 84" swing clearance
Siderails	14" x 26# Wide Flange Beam side rails
Tires	255/70R x 22.5 radials ; Wheel covers - 3/8" smooth plate w/ 1" traction bars
Wheels	10 hole steel disc; hub piloted
Axles & Brakes	(3) Rockwell 25,000#, 5" round axles; Brakes 16 1/2" x 7" x 3/4" service chambers; outboard drums; WABCO ABS (4S/2M) on two axles
Suspension	Hutch H9700TRI four point with 365-00 3 leaf heavy duty springs
Lights	Rubber mounted; sealed wiring harness; 7-way receptacle
Landinglegs	Holland Mark V; 2 speed with sand shoes; 62,500 lb lift capacity
Metal Covering	Metal covering with 1" traction bars is standard on the dovetail and over the axles. Steel covering is also standard on the motor grader approach ramps to the top deck.
Tiedowns	(18) D-rings total (4) located on the top deck and (14) located on the lower deck
Dovetail	5 ft. metal covered with 1" traction bars
Loading Ramps	7" Channel w/ 3/8" smooth plate and 1" traction bars; Hydraulic Assisted ramps that make raising and lowering a snap. The hydraulic unit is a 12-Volt self contained unit that is lever actuated.
Floor	2" nominal oak is standard. (Optional Flooring includes: Apitong, Shiplap Pine, Bamboo, Transdeck and Steel Sheeting)
D-Rings	18 total (14)-1" on rear deck, (4)-1" on front deck.
Finish	Shotblasted and painted using Polyurethane (DTM) Direct To Metal paint.(Standard colors are Black, Red and Cat Yellow) (Optional Epoxy or Zinc-Rich Primer)

OPTIONS

- HT 250US air ride suspension
- Fold-out outriggers (each)
- Increase to 9 ft wide
- Spare tire carrier between the beams on the neck

Dimensions

